

Technical drawing of a mechanical part, showing a front view and a section view A-A.

Front View Dimensions:

- Overall height: 21
- Top flange width: 6.5 ± 0.5
- Top flange thickness: 11.3 ± 0.2
- Distance from top flange to center of hole: 5.9 ± 0.2
- Distance from top flange to center of hole (alternative dimension): 9 ± 0.2
- Distance from top flange to center of hole (alternative dimension): 0.9
- Distance from top flange to center of hole (alternative dimension): 2.7 ± 0.2
- Distance from top flange to center of hole (alternative dimension): 4.7 ± 0.2
- Hole diameter: $\varnothing 4 \pm 0.1$

Section View A-A Dimensions:

- Overall width: 17 ± 0.2
- Distance from top flange to center of hole: 10 $+1$
- Minimum distance from top flange to center of hole: min. 7
- Fillet radius: R0.3 max.

Technical drawing of a tapered ramp (koniischer Auslauf) with dimensions: 3 ± 0.2 , $1 \times 30^\circ$, 0.5 , and 8.5 .

		1:1		
>400 ≤ 1000	±0,8			
>120 ≤ 400	±0,5			
> 30 ≤ 120	±0,3			
> 6 ≤ 30	±0,2			
≤ 6	±0,1			
Winkel Angle	±1°			
	fertig finished	roh raw		
Allgemeine Toleranzen fuer Nennmaesse ohne Toleranz. General tolerances for nominal dimensions without specified tolerance.			XXX	
Oberflaechenrauhheit Surface texture VW 13705		Werkstueckkanten Edge finish VW 01688		
Alle Maesse gelten fuer das Fertigteil einschliesslich Oberflaechenschutz. All dimensions apply to the finished part including surface protection.				

[illegible]