











RELEASE NUMBER	DATE	REVISION DESCRIPTION	BY	DATE	APPD
PA0398-16	-	-	INITIAL RELEASE	1/11	05/30/12





1. MATERIAL: CAST STEEL PER ASTM A148
GRADE 90-60
2. CAST P/N 16-19889-000 IN APPROXIMATE POSITION
SHOWN IN 6MM HIGH LETTERS RAISED 1MM. PLACE
FOUNDRY TRADEMARK ADJACENT TO PART NUMBER.
3. THIS DRAWING SHALL BE USED WITH THE 3D MODEL
FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS
NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED
FROM INTERROGATING THE 3D MODEL AND SHALL BE
INTERPRETED AS BASIC RELATIVE TO THE PRIMARY
REFERENCE FRAME UNLESS SUPERCEDED BY
A TOLERANCE OTHERWISE SPECIFIED IN THIS DRAWING.
4. CAST "FRONT" IN 10MM HIGH LETTERS RAISED 1MM.
5. DRAFT ANGLE; 3DEG UNLESS OTHERWISE NOTED.
6. FILLET RADIUS; 3.0 UNLESS OTHERWISE NOTED.
7. APPROXIMATE WEIGHT; 22 LBS.
8. TOLERANCES UNLESS OTHERWISE SPECIFIED:
LINEAR: $X = \pm 1.5$ X.X - ± 0.8
RADII: ± 1.5
ANGULAR: $\pm 1^\circ$
HOLES AND SLOTS: $\pm 0.4/-0.1$

ITEM NUMBER R16-19889-000		IDENTIFICATION	
SEAT-AXLE, 4P, 3.0D		SEAT-AXLE, 4P, 3.0D	
05/30/12 DATE 05/30/12 DATE 05/30/12 DATE 05/30/12 DATE 05/30/12 DATE		05/30/12 DATE 05/30/12 DATE 05/30/12 DATE 05/30/12 DATE	
THIRD ANGLE PERSPECTIVE 		THIRD ANGLE PERSPECTIVE 	
UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DEFINED ACCORDING TO ASME STANDARD Y14.3M-1994 (M)		UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DEFINED ACCORDING TO ASME STANDARD Y14.3M-1994 (M)	
1 OF 1 SHEET NUMBER		REV. 1/17/11 SHEET NUMBER	

DATE	BY	DESCRIPTION	REV	DATE	INITIALS	REVISION
05/31/12	LTA	INITIAL RELEASE	-	-	-	-
05/31/12	LTA	INITIAL RELEASE	-	-	-	-

1. MATERIAL: MACHINED FROM CASTING R16-19924-000.
2. IDENTIFY COMPONENT PER SPEC 49-00051.
3. SIMILAR TO P/N NONE.
4. TOLERANCES UNLESS OTHERWISE SPECIFIED:
 LINEAR: $X = \pm 1.5$ X.X = ± 0.8
 ANGULAR: $\pm 1^\circ$
 HOLES AND SLOTS: $+0.4/-0.1$





QUANTITY	ITEM NUMBER	DESCRIPTION	REF
1	R16-19924-000	BRKT-AXLE PCS5160, ZF 4P, RH	1

DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12
DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12






DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12
DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12

DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12
DATE	DATE	DATE	DATE	DATE	DATE
05/31/12	05/31/12	05/31/12	05/31/12	05/31/12	05/31/12

DATE	BY	DESCRIPTION	DATE	BY	DESCRIPTION
05/31/12	APD	INITIAL RELEASE	05/31/12	APD	INITIAL RELEASE





SECTION A-A



1. MATERIAL: CAST STEEL PER ASTM A148
GRADE 90-60.
2. CAST P/N 16-19924-000 IN APPROXIMATE POSITION
SHOWN IN 6MM HIGH LETTERS RAISED 1MM. PLACE
FOUNDRY TRADEMARK ADJACENT TO PART NUMBER.
3. THIS DRAWING SHALL BE USED WITH THE 3D MODEL
FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS
NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED
FROM INTERROGATING THE 3D MODEL AND SHALL BE
INTERPRETED AS BASIC RELATIVE TO THE PRIMARY
REFERENCE FRAME UNLESS SUPERCEDED BY
A TOLERANCE OTHERWISE SPECIFIED IN THIS DRAWING.
4. SIMILAR TO P/N NONE.
5. APPROXIMATE WEIGHT: 23.9 LBS.
6. UNLESS OTHERWISE SPECIFIED:
DRAFT ANGLE: 30DEG
CORNER RADIUS: 3.0
FILLET RADIUS: 5.0
7. TOLERANCES UNLESS OTHERWISE SPECIFIED:
LINEAR: $X = \pm 1.5$ X.X = ± 0.8
ANGULAR: $\pm 1^\circ$
HOLES AND SLOTS: $+0.4/-0.1$

ITEM NUMBER		R16-19924-000	
DESCRIPTION		BRKT-AXLE RS-19-144.4P, RH	
TOLERANCE NUMBER		62302	
REV. LETTER		-	
SHEET NUMBER		1 OF 1	
DATE		05/31/12	
THIRD ANGLE PROJECTION		M1	
UNLESS OTHERWISE NOTED, DIMENSIONS TO ARE STRAIGHT VIAL-SHAPED, WITH EXCEPTS PER GMA 9904-11037.		M1	
DATE		05/31/12	
DATE		05/31/12	
DATE		05/31/12	
DATE		05/31/12	










1. MATERIAL: MACHINED FROM CASTING R16-19924-000.
2. IDENTIFY COMPONENT PER SPEC 49-00051.
3. SIMILAR TO P/N NONE.
4. TOLERANCES UNLESS OTHERWISE SPECIFIED:
LINEAR: $X = \pm 1.5$ X.X = ± 0.8
RADII: ± 1.5
ANGULAR: $\pm 1^\circ$
HOLES AND SLOTS: $+0.4/-0.1$

QUANTITY	ITEM NUMBER	DESCRIPTION	REF
1	R16-19924-000	GRAT-AXLE RC25160, ZF 4P, RH	1

ITEM NUMBER		16-19924-000	
DESCRIPTION		BRKT - AXLE RS-19-144, 4P, RH	
ITEM NUMBER		16-19924	
REPLACEMENT DESCRIPTION		BRKT - AXLE RS-19-144, 4P, RH	
QUANTITY		62302	
REV. LETTER		-	
SHEET NUMBER		1 OF 1	

UNLESS OTHERWISE NOTED, DIMENSIONS TO AVERAGE SURFACES ARE GOVT AND ACCORDING TO AWE 91400-1994, WITH EXCEPTIONS PER DWA 99940-41037.		THIRD ANGLE PROJECTION		 		UNITED STATES OF AMERICA	
05/31/12	DATE	05/31/12	DATE	05/31/12	DATE	05/31/12	DATE

RELEASE NUMBER	REV	REV DATE	REVISION DESCRIPTION	BY	DATE	APP
PA0398-16	-	-	INITIAL RELEASE	LTA	05/31/12	TMB




1. MATERIAL: CAST STEEL PER ASTM A148
GRADE 90-60.
2. CAST P/N 16-19924-000 IN APPROXIMATE POSITION
SHOWN IN 6MM HIGH LETTERS RAISED 1MM. PLACE
FOUNDRY TRADEMARK ADJACENT TO PART NUMBER.
3. THIS DRAWING SHALL BE USED WITH THE 3D MODEL
FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS
NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED
FROM INTERROGATING THE 3D MODEL AND SHALL BE
INTERPRETED AS BASIC RELATIVE TO THE PRIMARY
REFERENCE FRAME UNLESS SUPERCEDED BY
A TOLERANCE OTHERWISE SPECIFIED IN THIS DRAWING.
4. SIMILAR TO P/N NONE.
5. APPROXIMATE WEIGHT: 23.9 LBS.
6. UNLESS OTHERWISE SPECIFIED:
DRAFT ANGLE: 30DEG
CORNER RADIUS: 3.0
FILLET RADIUS: 5.0
7. TOLERANCES UNLESS OTHERWISE SPECIFIED:
LINEAR: $X = \pm 1.5$ X.X = ± 0.8
ANGULAR: $\pm 1^\circ$
HOLES AND SLOTS: $+0.4/-0.1$

ITEM NUMBER		R16-19924-000	
DESCRIPTION		BRKT-AXLE RS-19-144.4P.RH	
SUBMITTAL DESCRIPTION		BRKT-AXLE RS-19-144.4P.RH	
62302		R16-19924	
SHEET NUMBER		1 OF 1	
DATE		05/31/12	
TIME		05/31/12	
PROJECTION		THIRD ANGLE	
UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DERIVED ACCORDING TO THE STANDARDS OF THE 1994-1995 EXCEPTIONS PER DPM 0990-11017.		UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DERIVED ACCORDING TO THE STANDARDS OF THE 1994-1995 EXCEPTIONS PER DPM 0990-11017.	

REV	DATE	BY	DESCRIPTION
1	05/31/12	LTA	INITIAL RELEASE
2	05/31/12	LTA	INITIAL RELEASE

REV	DATE	BY	DESCRIPTION
1	05/31/12	LTA	INITIAL RELEASE
2	05/31/12	LTA	INITIAL RELEASE







1. MATERIAL: MACHINED FROM CASTING R16-19923-000.
2. IDENTIFY COMPONENT PER SPEC 49-00051.
3. SIMILAR TO P/N NONE.
4. TOLERANCES UNLESS OTHERWISE SPECIFIED:
 LINEAR: $X = \pm 1.5$ $X.X = \pm 0.8$
 RADII: ± 1.5
 ANGULAR: $\pm 1^\circ$
 HOLES AND SLOTS: $+0.4/-0.1$

QUANTITY	ITEM NUMBER	DESCRIPTION	REF
1	R16-19923-000	BRKT-AXLE RS-19-144,4P,LH	1

REV	DATE	BY	DESCRIPTION
1	05/31/12	LTA	INITIAL RELEASE
2	05/31/12	LTA	INITIAL RELEASE

REV	DATE	BY	DESCRIPTION
1	05/31/12	LTA	INITIAL RELEASE
2	05/31/12	LTA	INITIAL RELEASE

1. IDENTIFY COMPONENT PER SPEC 49-00051.
2. REFERENCE FRAME A,B,C DEFINED ON ROUGH CASTING.
3. FINISH: PRIME PAINT PER SPEC 49-00023-102.
4. REQUIRED PRIOR TO PRODUCT AUTHORIZATION.
5. CALCULATED WEIGHT: 3.7KG (8.1LB) +






1107 NUMBER		16-17385-000
DESCRIPTION		BRKT-CONT ROD, 1BK, ALNR, AAC2N
REVISION DESCRIPTION		BRKT-CONT ROD, 1BK, ALNR, AAC2N
DRAWING NUMBER		16-17385
REV LETTER		B
REV NUMBER		1
D-SIZE		1
CATIA VS		1
DATE		01/10/11
DESIGNED BY		01/10/11
CHECKED BY		01/10/11
APPROVED BY		01/10/11
UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DEFINED ACCORDING TO ASME STRAIGHT V14.2M-1994, WITH DEVIATIONS FOR DIMS (9540-V1037).		
THIRD ANGLE PROJECTION		
DATE		01/10/11
DRAWN BY		01/10/11
CHECKED BY		01/10/11
APPROVED BY		01/10/11

DATE	01/10/11	TIME	10:00
REV	01/10/11	TIME	10:00
DATE	01/10/11	TIME	10:00
REV	01/10/11	TIME	10:00
DATE	01/10/11	TIME	10:00
REV	01/10/11	TIME	10:00
DATE	01/10/11	TIME	10:00
REV	01/10/11	TIME	10:00
DATE	01/10/11	TIME	10:00
REV	01/10/11	TIME	10:00

5. THIS DRAWING SHALL BE USED WITH THE 3D MODEL FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED FROM INTERROGATING THE 3D MODEL AND SHALL BE INTERPRETED AS BASIC RELATIVE TO THE PRIMARY DATUM REFERENCE FRAME UNLESS SUPERSEDED BY A TOLERANCE OTHERWISE SPECIFIED ON THE DRAWING.
4. IDENTIFY COMPONENT PER SPEC 49-00051.
CAST THE FOLLOWING INFORMATION:
PART NUMBER 16-17385-000 (6MM HIGH LETTERS RAISED 1MM)
DATE OF MANUFACTURE (3MM HIGH LETTERS RAISED 1MM)
PLACE VENDOR TRADEMARK OR IDENTIFICATION WITHIN 12MM DIA ADJACENT TO PART NUMBER.





3. LEAVE NO SHARP EDGES OR FINIS ON CASTING. INSIDE OF CASTING SHOULD BE CLEAN AND FREE OF CORE SAND AND FOREIGN MATTER.
2. FINISH: PRIME PAINT PER SPEC 49-00023-102.
1. MATERIAL: CAST STEEL ASTM-A27 GRADE 65-35
6. TOLERANCES UNLESS OTHERWISE SPECIFIED:
SURFACES: $\sqrt{3.0A|B|C}$
7. EST MASS = 3.9 KG (8.6 LB)
8. SURFACE FINISH: CAST SURFACE 12.5 $\sqrt{\text{MAX}}$
9. UNLESS OTHERWISE NOTED:
ALL FILLET RADIUS 6.0MM
DRAFT 3.0° MAX
FLASH NOT TO EXCEED 1.0MM MAX
MISMATCH 0.8MM MAX
10. APPROVAL OF SAMPLE PARTS REQUIRED PRIOR TO PRODUCTION AUTHORIZATION.
11. RESOURCING TO NEW SUPPLIERS MAY REQUIRE APPROVAL.
12. REMOVE ALL BURRS AND SHARP EDGES PER 49-00155.
13. PARTING LINE LOCATION TO BE APPROVED BY DTNA ENGINEERING PRIOR TO TOOLING CONSTRUCTION



ITEM NUMBER		R16-17385-000	
DESCRIPTION		BRKT-CONT ROD, 1BK, ALNR, AAC 2N	
DRAWING NUMBER		R16-17385	
REVISION		62307	
REV LETTER		B	
REV NUMBER		1 OF 1	
DATE		01/11/11	
THIRD ANGLE PROJECTION		YES	
UNLESS OTHERWISE NOTED, DIMENSIONS AND TOLERANCES ARE DEFINED ACCORDING TO ASME STANDARD Y14.5M-1994, WITH EXEMPTIONS PER OTHER DTDNO-V1037.		N/A	

REV	DATE	DESCRIPTION
1	01/11/11	1-REWORK IN VS
2		2-REVISED NOTE 4 FOR CLARITY
3		3-ADDED NOTES 6 THROUGH 13

1. MATERIAL: R16-17357-000.
2. IDENTIFY COMPONENT PER SPEC 49-00051.
3. (REFERENCE FRAME A,B,C DEFINED ON ROUGH CASTING.


3

1. MATERIAL: CAST STEEL ASTM-A27 GRADE 65-35
2. FINISH: PRIME PAINT PER SPEC 49-00023-102.
3. LEAVE NO SHARP EDGES OR FINS ON CASTING. INSIDE OF CASTING SHOULD BE CLEAN AND FREE OF CORE SAND AND FOREIGN MATTER.



7. EST MASS = 5.58KG (12.3 LB)
6. TOLERANCES UNLESS OTHERWISE SPECIFIED:
- SURFACES:  3.0A/B/C
5. THIS DRAWING SHALL BE USED WITH THE 3D MODEL FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED BY INTERPOLATING THE 3D MODEL AND SHALL BE INTERPRETED AS BASIC RELATIVE TO THE PRIMARY DATUM REFERENCE FRAME UNLESS SUPERSEDED BY A TOLERANCE OTHERWISE SPECIFIED ON THIS DRAWING.

SURFACES:  3.0 ABC

7. EST MASS = 5.58KG (12.3 LB)



150 VIEW
FOR REF ONLY

[illegible][illegible]R16-17357-000
CONT ROD. LATERAL, CAST

BRKT-CONT ROD, LATERAL, CAST

R16-17357

62307

BRKT-CONT ROD, LATERAL, CAST

10/00/01	DATE	10/01/00	DATE
----------	------	----------	------

DATE	03/19/03	PROJECT	AMC 6	NO. 1	REV.	01
------	----------	---------	-------	-------	------	----

DATE	08/26/05	THIRD		UNITED STATES OF AMERICA
------	----------	-------	---	--------------------------

03/16/50
JED

03/19/03
Date

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100 101 102 103 104 105 106 107 108 109 110 111 112 113 114 115 116 117 118 119 120 121 122 123 124 125 126 127 128 129 130 131 132 133 134 135 136 137 138 139 140 141 142 143 144 145 146 147 148 149 150 151 152 153 154 155 156 157 158 159 160 161 162 163 164 165 166 167 168 169 170 171 172 173 174 175 176 177 178 179 180 181 182 183 184 185 186 187 188 189 190 191 192 193 194 195 196 197 198 199 200 201 202 203 204 205 206 207 208 209 210 211 212 213 214 215 216 217 218 219 220 221 222 223 224 225 226 227 228 229 230 231 232 233 234 235 236 237 238 239 240 241 242 243 244 245 246 247 248 249 250 251 252 253 254 255 256 257 258 259 260 261 262 263 264 265 266 267 268 269 270 271 272 273 274 275 276 277 278 279 280 281 282 283 284 285 286 287 288 289 290 291 292 293 294 295 296 297 298 299 300 301 302 303 304 305 306 307 308 309 310 311 312 313 314 315 316 317 318 319 320 321 322 323 324 325 326 327 328 329 330 331 332 333 334 335 336 337 338 339 340 341 342 343 344 345 346 347 348 349 350 351 352 353 354 355 356 357 358 359 360 361 362 363 364 365 366 367 368 369 370 371 372 373 374 375 376 377 378 379 380 381 382 383 384 385 386 387 388 389 390 391 392 393 394 395 396 397 398 399 400 401 402 403 404 405 406 407 408 409 410 411 412 413 414 415 416 417 418 419 420 421 422 423 424 425 426 427 428 429 430 431 432 433 434 435 436 437 438 439 440 441 442 443 444 445 446 447 448 449 450 451 452 453 454 455 456 457 458 459 460 461 462 463 464 465 466 467 468 469 470 471 472 473 474 475 476 477 478 479 480 481 482 483 484 485 486 487 488 489 490 491 492 493 494 495 496 497 498 499 500 501 502 503 504 505 506 507 508 509 510 511 512 513 514 515 516 517 518 519 520 521 522 523 524 525 526 527 528 529 530 531 532 533 534 535 536 537 538 539 540 541 542 543 544 545 546 547 548 549 550 551 552 553 554 555 556 557 558 559 560 561 562 563 564 565 566 567 568 569 570 571 572 573 574 575 576 577 578 579 580 581 582 583 584 585 586 587 588 589 590 591 592 593 594 595 596 597 598 599 600 601 602 603 604 605 606 607 608 609 610 611 612 613 614 615 616 617 618 619 620 621 622 623 624 625 626 627 628 629 630 631 632 633 634 635 636 637 638 639 640 641 642 643 644 645 646 647 648 649 650 651 652 653 654 655 656 657 658 659 660 661 662 663 664 665 666 667 668 669 670 671 672 673 674 675 676 677 678 679 680 681 682 683 684 685 686 687 688 689 690 691 692 693 694 695 696 697 698 699 700 701 702 703 704 705 706 707 708 709 710 711 712 713 714 715 716 717 718 719 720 721 722 723 724 725 726 727 728 729 730 731 732 733 734 735 736 737 738 739 740 741 742 743 744 745 746 747 748 749 750 751 752 753 754 755 756 757 758 759 760 761 762 763 764 765 766 767 768 769 770 771 772 773 774 775 776 777 778 779 780 781 782 783 784 785 786 787 788 789 790 791 792 793 794 795 796 797 798 799 800 801 802 803 804 805 806 807 808 809 810 811 812 813 814 815 816 817 818 819 820 821 822 823 824 825 826 827 828 829 830 831 832 833 834 835 836 837 838 839 840 841 842 843 844 845 846 847 848 849 850 851 852 853 854 855 856 857 858 859 860 861 862 863 864 865 866 867 868 869 870 871 872 873 874 875 876 877 878 879 880 881 882 883 884 885 886 887 888 889 890 891 892 893 894 895 896 897 898 899 900 901 902 903 904 905 906 907 908 909 910 911 912 913 914 915 916 917 918 919 920 921 922 923 924 925 926 927 928 929 930 931 932 933 934 935 936 937 938 939 940 941 942 943 944 945 946 947 948 949 950 951 952 953 954 955 956 957 958 959 960 961 962 963 964 965 966 967 968 969 970 971 972 973 974 975 976 977 978 979 980 981 982 983 984 985 986 987 988 989 990 991 992 993 994 995 996 997 998 999 1000 1001 1002 1003 1004 1005 1006 1007 1008 1009 1010 1011 1012 1013 1014 1015 1016 1017 1018 1019 1020 1021 1022 1023 1024 1025 1026 1027 1028 1029 1030 1031 1032 1033 1034 1035 1036 1037 1038 1039 104

0-512E

L

2

3

7

5

9

/

Q

V

B

2

9

V

C

7

5

12

C



1

REVISING NUMBER	DATE	REVISION DESCRIPTION	BY	DATE
PHOTO-28-10	A	INITIAL RELEASE TO PRODUCTION	AVG	11/13/95
PHOTO-28-55	B	UPDATE REV LEVEL TO AGREE	DRV	05/26/97
		WITH MACHINE DRAWING		
PHOTO-14-H	C	UPDATED DRAWING TO CURRENT	SJT	09/26/05
		GD & STANDARD		

MATERIAL: CAST STEEL, ASTM-A27 GRADE 65-35

2. LEAVE NO SHARP EDGES OR FINS ON CASTING. INSIDE OF CASTING SHOULD BE CLEAN AND FREE OF CORE SAND AND FOREIGN MATTER.

IDENTIFY COMPONENT PER SPEC 49-00051.

CAST MACHINE PART NUMBER WITH 6MM HIGH LETTERS,
RAISED IMM AND DATE OF MANUFACTURE WITH 9.5MM HIGH
LETTERS, RAISED IMM, PLACE VENDOR TRADEMARK OR
IDENTIFICATION WITHIN 25MM DIA ADJACENT TO PART NUM

4. THIS DRAWING SHALL BE USED WITH THE 3D MODEL FOR COMPLETE PRODUCT DEFINITION. DIMENSIONS NOT DISPLAYED ON THIS DRAWING SHALL BE DERIVED BY INTERROGATING THE 3D MODEL AND SHALL BE INTERPRETED AS BASIC RELATIVE TO THE PRIMARY DATUM REFERENCE FRAME UNLESS SUPERSEDED BY A TOLERANCE OTHERWISE SPECIFIED ON THIS DRAWING.


5. TARGETS ARE DEFINED IN THE 3D CAD MODEL.

6. TOLERANCES UNLESS OTHERWISE SPECIFIED:





SURFACES:  3, 0 A B C

7. FINISH; PRIME PAINT PER SPEC 49-00023-102


SECTION J-J








SECTION K-K

[illegible]

1. MATERIAL: R16-21455-000
2. IDENTIFY COMPONENT PER SPEC 49-00051
3. SURFACE FINISH: MACHINED SURFACE 3.2 MAX
4. CALCULATED WEIGHT = 6.97kg (13.13 lbs)
5. REMOVE ALL BURRS AND SHARP EDGES PER SHOP PRACTICE 49-00155.
6. REQUIRED PRIOR TO PRODUCTION AUTHORIZATION
7. RESOURCING TO NEW SUB SUPPLIERS MAY REQUIRE FTL ENGINEERING APPROVAL
8. REFERENCE FRAME A,B AND C DEFINED ON









ISOMETRIC VIEW
FOR ENGINEERING REFERENCE ONLY



Item Number	BRK-LTL-LH-LD-6-A1-B1-390
Description	Bracket




1. MATERIAL : P16-21455-000
2. IDENTIFY COMPONENT PER SPEC 49-0051.
3. SURFACE FINISH MACHINED SURFACE
4. CALCULATED WEIGHT = 5.21kg (11.45lbs)
5. REMOVE ALL BURRS AND SHARP EDGES PER SHOP PRACTICE 49-0055.
6. IF SAMPLE PARTS
REQUIRED PRIOR TO PRODUCTION AUTHORIZATION.
7. RESOURCING TO NEW SUB SUPPLIERS MAY
REQUIRE FTL ENGINEERING APPROVAL.
8. REFERENCE FRAME A,B AND C DEFINED ON
ROUGH CASTING

[illegible]




Item Number	Description
16-21456-000	BECKF LIT AL AET A184-2-350

[illegible]

-000 (FWD) SHOWN
-001 (AFT) OPPOSITE



1. MATERIAL: R16-21346-000.
2. IDENTIFY COMPONENT PER SPEC 49-00051.
3. REFERENCE FRAME A, B, C DEFINED ON ROUGH CASTING.
4. MANUFACTURER TO ESTABLISH PRODUCTION PART PRODUCTION ENGINEERING APPROVAL CONTROL PLAN.
5. |
6. RESOURCING TO NEW SUPPLIERS REQUIRE APPROVAL.
7. WEIGHT 7.09 kg (15.6 lb) USING A DENSITY OF 7800 kg/m³.

[illegible]

16-21346-000	BRKT:VROD,AXLE MTD,GTT,RR,RTS2
Item Number	Description

